CAPTEC

IC-425-B 2U RACK COMPUTER FOR INDUSTRIAL APPLICATIONS

KEY BENEFITS

- Latest Intel 7th generation processors deliver increased performance and efficiency
- Maintenance-free industrial design, our most cost-effective IC solution
- Chassis intrusion switch (programmable with G and S motherboards) safeguards the system from undetected interference
- Unobstructed airflow design delivers excellent thermal capabilities
- Isolated drive cages protect internal components from mechanical disk vibration damage
- Front panel LAN indicators enable network activity monitoring



The new IC-425-B-series from Captec is our most cost-effective off-the-shelf 2U platform.

Offering a combination of high airflow, increased storage and strong security features in a short depth 2U chassis, the IC-425-B series is an ideal fit for security applications such as CCTV where 24/7 operation in a clean unmanaged environment is required.

Each model incorporates robust industrial-grade components designed for 24/7 operation and is backed by extended platform longevity.












SPECIFICATIONS

IC-425-B	Chassis Specification	IC-425-B	Chassis Specification
Key Features	Chassis intrusion switch Cushioned HDD cages Front panel LAN indicators	Width & Mounting	19" Rackmount (optional sliding rails)
		Dimensions	430 x 88 x 457 (mm)
Disks	1 x 5.25" External bay 1 x 3.5" External drive bay	Weight	9.4kg (gross)
		Storage Temperature	-20°C to 70°C
Input Voltage	2 x 3.5" / 2 x 2.5" Internal drive bays AC 90~264V	Expansion Slots	7 Low profile or 3 full height (varies with motherboard)
Input Frequency	50 / 60 Hz	Storage	Up to 2 x 3.5" and 2 x 2.5" HDD or SSD
PSU	400W 80+ Gold	Ingress	No filter
Fans	1 x 80mm Fan (1 x 80mm rear optional)	Certification	CE
IC-425-B	Motherboard Specification		
16-429-В	IC-425-BG	IC-425-BS	IC-425-BB
CPU	Intel Celeron G3900, Intel Core i3-6100, Intel Core i5-6500, Intel Core i7-6700, Intel Celeron G3930, Intel Core i3-7101E, Intel Core i5-7500, Intel Core i7-7700		
Chipset	Intel Q170	Intel H110	Intel B150
Memory	4 x DDR4 2400MHz (2133MHz with 6th Gen CPU) UDIMM (up to 64GB)	2 x DDR4 2400MHz (2133MHz with 6th Gen CPU) UDIMM (up to 32GB)	
Graphics	Intel HD graphics with multi-display support (graphics vary depending on CPU, add-in graphics cards supported)		
LAN	1 x Intel I210 / 1 x Intel I219LM	1 x Intel I219LM	1 x Realtek RTL8111G
Expansion	1 x PCIe x16 (PCIe 3.0 support) 1 x PCIe x1, 1 x PCIe x8, 1 x PCIe x4, 3 x PCI	1 x PCIe x16 (PCIe 3.0 support) 1 x PCIe x1, 1 x PCIe x4, 3 x PCI	1 x PCle x16 (PCle 3.0 support) 2 x PCle x1
Display	1 x VGA, 3 x DisplayPort		1 x DVI-D, 2 x DisplayPort
Rear I/O	2 x RS232/422/485, 4 x USB 3.0 2 x LAN, Audio, PS/2 Combo	1 x RS232, 1 x RS232/422/485 4 x USB 3.0, 1 x LAN, PS/2 Combo	4 x USB 2.0, 2 x USB 3.0, 1 x LAN PS/2 Mouse, PS/2 Keyboard
Internal Connectors	2 x USB 3.0, 6 x USB 2.0, 4 x RS232 6 x SATA 3.0, 1 x mSATA, 1 x mPCle 1 x Parallel, 8 x GPI + 8 x GPO	6 x USB 2.0, 2 x RS232 4 x SATA 3.0, 1 x mSATA 1 x Parallel, 8 x GPI + 8 x GPO	2 x USB 3.0, 4 x USB 2.0 1 x RS232, 4 x SATA 3.0
Storage	1 x mSATA, 6 x SATA (RAID 0,1,5,10)	1 x mSATA, 4 x SATA	4 x SATA
Audio	Mic-in, line-in, line-out		
Operating System	Microsoft Windows 7 / Windows 8 / Windows 10 / Windows Server 20xx / Linux (configuration support optional)		
Operating Temperature	0°C to 60°C		0°C to 40°C
Expected Discontinuance	Q3 2030	Q3 2030	Q1 2019

TECHNICAL DETAILS







Top View

Side View

Microsoft Partner

E&OE. Captec reserves the right to change specifications without notice.

CAPTEC

EMEA Office

7 Whittle Avenue, Fareham Hants, PO15 5SH, UK

T: +44 (0)1489 866 066 F: +44 (0)1489 866 088 E: sales@uk.captec-group.com

in /company/captec

www.captec-group.com

North America Office 15 Saltsman Dr. Cambridge, ON. N3H 4R7, Canada

T: +1 (519)650-4000 F: +1 (519)650-2000 E: sales@ca.captec-group.com

🥑 @Captecgroup



161219-1 © Captec Ltd. 2018 All rights reserved - All products and company names listed are trademarks or trade

names of their respective companies

(intel)





PARTNER GOLD

OEM