

GETAC ZX70

7-INCH RUGGED TABLET

KEY BENEFITS

- ▶ Ideal for in-vehicle applications
- ▶ Protected for use in harsh environments
- ▶ Easy outdoor usability
- ▶ Powered by Android
- ▶ Comfortable and lightweight
- ▶ Customisable data capture



Ideal for mobile workforce and in-vehicle applications in challenging environments. Deploy the Getac ZX70 7-inch rugged Android tablet with confidence knowing it has been tested for extreme conditions and proven by MIL-STD-810G with IP67 ingress protection.



SPECIFICATIONS

Getac ZX70	7-inch Rugged Tablet
Display	7" HD (1280 x 720) LumiBond® 2.0 outdoor-readable display
Touch	Glove capable capacitive multi-touch
CPU	Intel® Atom Processor x5-Z8350 1.44 GHz
Memory	Up to 4GB LPDDR3
Storage	Up to 64GB eMMC
Expansion	Mutually exclusive: UHF RFID reader, 4G LTE, 1D/2D barcode reader. RFID/NFC combo reader
Connectivity	Wireless LAN 802.11n, Bluetooth 4.0, dedicated GPS, optional 4G LTE
I/O	USB 2.0 (host), MicroUSB 2.0 (client), optional RF antenna dual pass-through
Camera	Front FHD webcam, 8MP auto-focus rear camera
Operating System	Android 6.0

Getac ZX70	7-inch Rugged Tablet
Mounting	Mountable in a wide range of vehicles
Dimensions	218mm W x 142mm H x 27mm D
Weight	0.78kg
Operating Temperature	-21°C - 60°C
Storage Temperature	-40°C - 71°C
Shock/Drop	MIL-STD-810G, 6 feet drop resistant
Vibration	Vibration resistant
Ingress Protection	IP67 (IEC-60529)
In-vehicle	eMark
Ordering Information	ZX70

TECHNICAL DETAILS



E&OE. Captec reserves the right to change specifications without notice.

CAPTEC

EMEA Office
7 Whittle Avenue, Fareham
Hants, PO15 5SH, UK

T: +44 (0)1489 866 066
F: +44 (0)1489 866 088
E: sales@uk.captec-group.com

[in](#) /company/captec

www.captec-group.com

North America Office
15 Saltzman Dr. Cambridge,
ON. N3H 4R7, Canada

T: +1 (519)650-4000
F: +1 (519)650-2000
E: sales@ca.captec-group.com

[t](#) @Captegroup



180412-1 © Captec Ltd. 2018 All rights reserved - All products and company names listed are trademarks or trade names of their respective companies

