

- Latest Intel 7th generation processors deliver increased performance and efficiency
- Lockable front door to prevent unauthorised access to power switches and I/O
- Chassis intrusion switch (programmable with G and S motherboards) safeguards the system from undetected interference
- Removable front fan and filter reduces servicing time and increases product life
- Isolated drive cages protect internal components from mechanical disk vibration damage
- Front panel LAN indicators enable network activity monitoring



The new IC-425-S series from Captec is our most versatile off-the-shelf 2U platform. It combines the largest storage capacity of the IC range with a full complement of chassis security features and easily serviceable dust particle fan filters.

These attributes make the IC-425-S series ideally suited to communications and higher education applications where space is at a premium and secure storage is required.

Each model incorporates robust industrial-grade components designed for 24/7 operation and is backed by extended platform longevity.










SPECIFICATIONS


IC-425-S	Chassis Specification
Key Features	Lockable door Chassis intrusion switch Cushioned HDD cages Front panel LAN indicators
Disks	1 x 5.25" External bay 1 x 3.5" External drive bay 2 x 3.5" / 2 x 2.5" Internal drive bays
Input Voltage	AC 90~264V
Input Frequency	50 / 60 Hz
PSU	400W 80+ Gold
Fans	1 x 80mm Fan (1 x 80mm rear optional)


IC-425-S	Chassis Specification	
Width & Mounting	19" Rackmount (optional sliding rails)	
Dimensions	430 x 88 x 457 (mm)	
Weight	9.4kg (gross)	
Storage Temperature	-20°C to 70°C	
Expansion Slots	7 Low profile or 3 full height (varies with motherboard)	
Storage	Up to 2 x 3.5" and 2 x 2.5" HDD or SSD	
Ingress	Air filter	
Certification	CE	

IC-425-S	Motherboard Specification		
	IC-425-SG	IC-425-SS	IC-425-SB
СРИ	Intel Celeron G3900, Intel Core i3-6100, Intel Core i5-6500, Intel Core i7-6700, Intel Celeron G3930, Intel Core i3-7101E, Intel Core i5-7500, Intel Core i7-7700		
Chipset	Intel Q170	Intel H110	Intel B150
Memory	4 x DDR4 2400MHz (2133MHz with 6th Gen CPU) UDIMM (up to 64GB) 2 x DDR4 2400MHz (2133MHz with 6th Gen CPU) UDIMM (up to 32GB)		
Graphics	Intel HD graphics with multi-display support (graphics vary depending on CPU, add-in graphics cards supported)		
LAN	1 x Intel I210 / 1 x Intel I219LM	1 x Intel I219LM	1 x Realtek RTL8111G
Expansion	1 x PCle x16 (PCle 3.0 support) 1 x PCle x1, 1 x PCle x8, 1 x PCle x4, 3 x PCl	1 x PCle x16 (PCle 3.0 support) 1 x PCle x1, 1 x PCle x4, 3 x PCl	1 x PCle x16 (PCle 3.0 support) 2 x PCle x1
Display	1 x VGA, 3 x DisplayPort		1 x DVI-D, 2 x DisplayPort
Rear I/O	2 x RS232/422/485, 4 x USB 3.0 2 x LAN, Audio, PS/2 Combo	1 x RS232, 1 x RS232/422/485 4 x USB 3.0, 1 x LAN, PS/2 Combo	4 x USB 2.0, 2 x USB 3.0, 1 x LAN PS/2 Mouse, PS/2 Keyboard
Internal Connectors	2 x USB 3.0, 6 x USB 2.0, 4 x RS232 6 x SATA 3.0, 1 x mSATA, 1 x mPCle 1 x Parallel, 8 x GPI + 8 x GPO	6 x USB 2.0, 2 x RS232 4 x SATA 3.0, 1 x mSATA 1 x Parallel, 8 x GPI + 8 x GPO	2 x USB 3.0, 4 x USB 2.0 1 x RS232, 4 x SATA 3.0
Storage	1 x mSATA, 6 x SATA (RAID 0,1,5,10)	1 x mSATA, 4 x SATA	4 x SATA
Audio	Mic-in, line-out		
Operating System	Microsoft Windows 7 / Windows 8 / Windows 10 / Windows Server 20xx / Linux (configuration support optional)		
Operating Temperature	0°C to 60°C		0°C to 40°C
Expected Discontinuance	Q3 2030	Q3 2030	Q1 2019

TECHNICAL DETAILS







E&OE. Captec reserves the right to change specifications without notice.

CAPTEC

EMEA Office 7 Whittle Avenue, Fareham Hants, PO15 5SH, UK

T: +44 (0)1489 866 066 F: +44 (0)1489 866 088 E: sales@uk.captec-group.com

in /company/captec

www.captec-group.com

North America Office 15 Saltsman Dr. Cambridge, ON. N3H 4R7, Canada

T: +1 (519)650-4000 F: +1 (519)650-2000

E: sales@ca.captec-group.com





















