

FZ-A2

PANASONIC TOUGHPAD

KEY BENEFITS

- ▶ Ideal for in-vehicle applications
- ▶ Protected for use in harsh environments
- ▶ Work through a full shift with hot swappable batteries
- ▶ Easy outdoor usability with an IPS, 800nit display
- ▶ Flexible data capture



Deploy the FZ-A2 across your entire fleet with confidence knowing it's been tested to Panasonic's high standards. Ideal for Microsoft Windows field work applications, the FZ-A2 supports legacy I/O options via its unique configuration port.



SPECIFICATIONS

FZ-A2	Panasonic Toughpad
CPU	Intel Atom x5-Z8550
Display	10.1" WUXGA (1920x1200) IPS outdoor display (up to 800cd/m ²)
Memory	4GB
Storage	32GB eMMC
Graphics	Mountable in a wide range of vehicles – VESA 75mmx75mm
I/O	1x USB 3.0, 1x USB 3.1 type C, 1x HDMI, 1x headset, 1x external antenna (Optional)
Optional I/O	2D barcode reader, smart card reader
GNSS	Integrated
Mobile Data	Optional 3G LTE (GOBI 5000)
Wireless	Intel dual band wireless-AC 8260, Bluetooth 4.4 + EDR Class 1

FZ-A2	Panasonic Toughpad
Operating System	Android 6.0
Battery	Li-Ion (2720mAh at 11.4V)
Input Voltage	16V DC, 4.06A
Dimensions	272mm (W) x 196mm (H) x 16.4mm (D)
Weight	Approximately 880g
Operating Temp.	-29°C to 60°C
Storage Temp.	-51°C to 71°C
Drop	MIL-STD-810G, 120cm
Ingress Protection	IP65
Ordering Information	Panasonic Toughpad FZ-A2 default configuration

KEY FEATURES

LARGE 10.1-INCH DISPLAY

IP-65 INGRESS PROTECTION

2D BARCODE MODULE

HOT SWAPPABLE BATTERIES



E&OE. Captec reserves the right to change specifications without notice.

CAPTEC

EMEA Office
7 Whittle Avenue, Fareham
Hants, PO15 5SH, UK

T: +44 (0)1489 866 066
F: +44 (0)1489 866 088
E: sales@uk.captec-group.com

[in](#) /company/captec

www.captec-group.com

North America Office
15 Saltzman Dr. Cambridge,
ON. N3H 4R7, Canada

T: +1 (519)650-4000
F: +1 (519)650-2000
E: sales@ca.captec-group.com

[@Captecgrou](#)



180830-1 © Captec Ltd. 2018 All rights reserved - All products and company names listed are trademarks or trade names of their respective companies

